A. NETWORK DESIGN

a.	Proposed NCore Station #1	NEW SITE	X EXISTING SITE AQS #16-001-0010
b.	Proposed NCore Station #2	NEW SITE	EXISTING SITE AQS #
c.	Proposed NCore Station #3	NEW SITE	EXISTING SITE AQS #

	Item	Criteria	Status	Next Steps
1	Urban or Rural? Urban	Largest MSA(s) covered by urban station. Boise City		
2	Scale of Representation	Neighborhood X Urban Regional Other		Neighborhood scale or larger highly recommended.
3	Population Oriented	Yes X No	Population Exposure	Population oriented monitoring highly recommended.
4	Proximity to local emissions sources	No biasing local sources within 500 meters for urban stations. No biasing sources or large urban population centers within 50 km for rural stations.	Highway is 303.4 meters away from site (GIS)	
5	Suitability for meteorological measurements	Distance from obstructions is 10x height of obstruction above station. See Volume IV: Meteorological Measurements Version 1.0 (Draft)	Closest obstructions: buildings (W & NW) - the closest is 212.3 meters, or 7x height of obstruction	
6	Information (including site photographs) provided for AMTIC NCore web site	Photographs in 8 cardinal directions needed.	See attached photos; electronic version is on CD provided	
7	Station Coordinates	Determined by GPS	43.607568 -116.348434	
8	Site visited by EPA in past 3 years	Meets applicable Appendix D and E criteria.	Yes; May 20, 2008	New sites should be visited by EPA before final NCore approval is requested

	Item	Criteria	Status	Next Steps
9	Network leveraging	Collocation with other networks encouraged: STN X Supplemental CSN NATTS CASTNET IMPROVE NADP PAMS Other	Speciation trends monitor located at same site	
10	Applicable site fields updated in AQS including coordinates	Consider setting additional monitor type to "Proposed NCore" (station should also be categorized as SLAMS).	All St. Luke's monitors have been set up as Proposed NCORE	
		LOGISTICAL CONSI	DERATIONS	
11	Site access	Access for at least five years is suggested.	Criteria met	
12	Power requirements and availability	200A service suggested. 240vac service typically needed for a/c. Key power outlets protected by UPS units.	Criteria met; all outlets are surge protected	
13	Telecommunications	Minimum dial-up service. Broadband service suggested for polling of 1-minute data.	Raven cellular modems being used with IP addresses	
14	A/C cooling capacity	Minimum 18,000BTU a/c capacity.	Criteria met	
15	Interior space	Sufficient for minimum of two 19" inner dimension, 6' tall instrument racks and related equipment and accessories, or equivalent shelf space.	Criteria met	

	Item	Criteria	Status	Next Steps
16	Exterior space (roof and	Allow for:	A shelter is located at the	
	accompanying platforms)	a) 1m spacing of low-volume PM	site; the roof is used for	
		sampler inlets – up to seven*	the speciation monitor.	
		required plus PEP audit sampler.	Next to the shelter is a	
		b) 1m spacing between low-volume	wooden platform allowing	
		PM sampler inlets and gas manifold	1m spacing of PM _{2.5}	
		cane or Teflon tubing.	FRMs.	
		Facilitate usage of TTP audit		
		vehicle or trailer.		
17	10m tower compatibility	Required for meteorological	A 10m met tower is on	
		equipment, NOy converter. Room	site, but a 10m mast will	
		to drop tower for calibrations and	be attached to the shelter	
		audits.	for the NO _y converter	

^{*}Notes

- 1. PM2.5 FRM sampler
- 2. PM10c FRM sampler for PM10-2.5 mass (dichotomous sampler could substitute for #1 and #2 if future FRM/FEMs available) or PM10-2.5 continuous
- 3. PM2.5 continuous sampler (does not have to be FEM/ARM)
- 4. PM2.5 speciation sampler (CSN or IMPROVE)
- 5. URG sampler for carbon channel (PM2.5 speciation) if using CSN samplers
- 6. Sampler for PM10-2.5 speciation (unless dichotomous sampler or PM2.5 speciation sampler (spare channels) is used)
- 7. URG sampler for PM10 carbon speciation (speculative need for PM10-2.5 carbon speciation by difference)

B. REQUIRED PARAMETER/METHODOLOGICAL EVALUATION

d.	Proposed NCore Station #1	NEW SITE	X EXISTING SITE AQS # 16-001-0010	
e.	Proposed NCore Station #2	NEW SITE	EXISTING SITE AQS #	
f.	Proposed NCore Station #3	NEW SITE	EXISTING SITE AQS #	

	Parameter	Existing Me	Existing Measurements		easurements	Notes
		Sampling Began	Method	Date Expected	New or Relocated	
1	Ozone	5/01/07	087 - Teledyne			Year-round
			API, Model			operation
			400E			As of 5/01/08
2	Sulfur dioxide			7/01/08	API M100EU	High sensitivity
3	Carbon monoxide			7/01/08	API M300EU	High sensitivity
					Ultra (CE)	
4	Nitrogen oxides (NOy)*			7/01/08	API M200EU	High sensitivity
						External converter
						mounted at 10m
5	PM2.5 mass	9/26/06	R&P Manual			1-in-3 day
			until 10/19/07;			FRM/FEM
			now Sequential			integrated Now 1:6
6	PM2.5 continuous	7/01/06	R&P PM _{2.5}			FEM or ARM
			TEOM AB			preferred but not
						required It is not
						designated
7	PM2.5 speciation	7/01/06	MetOne SASS			1-in-3 day (Met One
			URG 3000			& URG 3000N
						samplers) or
						IMPROVE Now 1:3
8	PM10-2.5 mass			7/01/08		Integrated samplers
						(FRM difference or
						dichot) or continuous
						monitor Two FRMs

	Parameter	Existing Mea	asurements	Future Measurements		Notes
		Sampling Began	Method	Date Expected	New or Relocated	
9	PM10-2.5 speciation					Details to be
						provided later (2008)
						on sampling
						requirements.
10	Wind speed and direction**			7/01/08		At 10 m Working
11	Ambient temperature**			7/01/08		At 2 m on power
12	Relative humidity**			7/01/08		At 2 m & comm-
13	Optional – Vertical wind speed,			7/01/08		unications
	solar radiation, precipitation,					
	barometric pressure, delta-T for					
	2-10m.					
14	Optional – Ammonia and nitric					Pilot project using
	acid					denuders scheduled
						for 2008-2009.

Notes

^{*} Although the measurement of NOy is required in support of a number of monitoring objectives, available commercial instruments may indicate little difference in their measurement of NOy compared to the conventional measurement of NOx, particularly in areas with relatively fresh sources of nitrogen emissions. Therefore, in areas with negligible expected difference between NOy and NOx measured concentrations, the Administrator may allow for waivers that permit high-sensitivity NOx monitoring to be substituted for the required NOy monitoring at applicable NCore sites.

^{**} EPA recognizes that, in some cases, the physical location of the NCore site may not be suitable for representative meteorological measurements due to the site's physical surroundings. It is also possible that nearby meteorological measurements may be able to fulfill this data need. In these cases, the requirement for meteorological monitoring can be waived by the Administrator.

C. SUPPORTING EQUIPMENT EVALUATION

a.	Proposed NCore Station #1	NEW SITE	X EXISTING SITE AQS # 16-001-0010
b.	Proposed NCore Station #2	NEW SITE	EXISTING SITE AQS #
c.	Proposed NCore Station #3	NEW SITE	EXISTING SITE AQS #

	Item	Criteria	Status	Next Steps
1	Calibrator (field)	Suitable for trace-level dilutions, see Appendix A audit concentrations. Capable of automated QC checks. Internal O3 generator – photometer preferred.	Have the API 700 Multi-gas calibrator	Need to do acceptance testing & set-up on site Will be used for MDL-level concentrations
2	Calibrator (lab or field)	Suitable for generation of MDL-level concentrations	Will have API 700 in the lab & at the site	
3	Zero Air Source	Compliant with TAD recommendations. Ultra-pure air cylinder recommended for occasional comparison to zero air source. Capacity for 20+ LPM of dilution air.	Using ultra-pure air cylinders from Scott-Marin in CA We have the capacity for 20+ LPM of dilution air	
4	Data acquisition system	Digital-capable system	Campbell Scientific CR23X & two Raven cellular modems	
5	Gas cylinder standards	Suitable for trace-level dilutions, see Appendix A audit concentrations, EPA Protocol certifications. Special low- level standards needed for MDL concentrations (CO, SO2, NOy)	The gases are special low-level standards that meet EPA specifications	
6	Meteorological calibration devices	Provide NIST traceability of required meteorological parameters.		Assessment of calibration equip. & upgrade where needed
7	Sampling manifold	Per Appendix E. Residence time <20 seconds, only glass or Teflon materials, probe and monitor inlets acceptable heights.	Criteria met	

8	Auditing equipment	Independent calibrator, zero air source	State Lab's equipment is	
		and gas standards compatible with trace	independent & is compatible	
		level specifications. Independent	with trace-level specifications	
		meteorological and flow standards, it		
		not already available.		

D. ORGANIZATIONAL FACTORS

	Item	Criteria	Status	Next Steps
1	Training considerations	Key monitoring personnel have attended OAQPS provided monitoring workshops or equivalent training.		Trace gas training to be provided by API in June 2008
2	Monitoring station documentation	NCore station(s) described in Annual Monitoring Network Plan.	Described in this worksheet, the 2008 Annual Network Plan, and next year's Annual Network Plan if needed	Must be included in plan due on or before July 1, 2009. Discuss siting with health researchers and other data stakeholders.
3	Section 103 funds received and obligated for equipment purchases			Work with EPA Regional contacts.















